



ALPHA OIL



Product Catalog



ALPHA OIL

SYNTHETIC FLUID

PCMO

HDDO

HYDRAULIC

GEAR OIL

MOTORCYCLE OIL

TRANSMISSION

GREASES



ABOUT US.

ALPHA OIL is a leading brand of innovation, formulation and provision of high performance lubricants enabling and improving your vehicles life. We bring proven experience, deep technical knowledge and intense customer focus to bear on our customer's toughest challenges, adding tangible value to products in a wide range of industries and applications.

We use most up to date spectrum analysis and ASTM test, which enable us to provide outstanding consultancy services to our customer. ALPHA OIL brand is internationally recognized and trusted for its high performance and it is also known for its consistent quality and competitive pricing. We have the ISO Certified production facility and storage capacity in United Arab Emirates to provide uninterrupted supply and prompt short notice delivery.

Range of Products

DIESEL ENGINE OIL	04
PETROL ENGINE OIL	13
MOTOCYCLE ENGINE OIL	20
CNG ENGINE OIL	22
AUTOMATIC TRANSMISSION OIL.....	23
AUTOMOTIVE GEAR OIL	26
AUTOMOTIVE BRAKE FLUID	29
COOLANT	30
INDUSTRIAL GEAR OIL	31
HYDRAULIC OIL	32
GREASES	33



DIESEL ENGINE OIL

SAE GRADE: 0W-30 / 0W-40 / 5W-30 / 5W-40 / 10W-30 / 10W-40 / 15W-40

API: CK-4/SN

SYNTHETIC / SEMI SYN / MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL CK-4/SN is a low ash heavy duty engine oil that helps extend engine life in the most severe on and off-highway applications while delivering outstanding performance in modern high output low-emission engines fitted with EGR, DPF, DOC and SCR - Adblue NOx reduction systems. The exceptional low temperature fluidity and pump ability in combination with the sophisticated additive system ensures maximum engine wear performance and supports longer engine life.</p>	<ul style="list-style-type: none"> • API CK-4/SN • Caterpillar ECF-3 • Volvo VDS-4.5 • Cummins CES 20086 • MB 228.31 • ACEA E9 -16 • Deutz DQC III-10 LA • Renault RLD-3 • Ford WSS-M2C171-F1 • Mack EOS-4.5 • MAN M3775 • DDC 93K222 • MTU Type 2.1

Available in





DIESEL ENGINE OIL

SAE GRADE: 0W-30 / 0W-40 / 5W-30 / 5W-40

API: CJ-4/SN

FULLY SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL CJ-4/SN is an advanced synthetic, high performance heavy duty diesel engine oil that helps extend engine life and improve fuel economy in modern diesel engines operating in severe conditions. The latest Low SAPS additive technology helps protect the poisoning of exhaust after-treatment devices and maintains vehicle emission compliance and engine fuel efficiency. Suitable for both latest low emissions and older model vehicles.</p>	<ul style="list-style-type: none"> • API CJ-4/SN • ACEA E9 • MB 228.31 • Caterpillar ECF-3 • MAN M3477/3575 • VOLVO VDS-4 • Renault RLD-3 • DDC 93K218 • Mack EO-O PP • Cummins CES 20081 • DEUTZ DQC III-10 LA • FORD WSS-M2C171-F1

SAE GRADE: / 10W-30 / 10W-40

API: CJ-4/SN

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL CJ-4/SN is a premium performance semi synthetic low emission heavy-duty engine oil designed for naturally aspirated and turbocharged four-stroke diesel and petrol engines in on- and off-highway and construction machinery applications. It is formulated with a range of latest technology dispersant, detergent, oxidation inhibition, anti-wear, anti-corrosion, viscosity improver and foam suppression additives and is recommended for extended drain intervals.</p>	<ul style="list-style-type: none"> • API CJ-4/SN • ACEA E9 • MB 228.31 • Caterpillar ECF-3 • MAN M3477/3575 • VOLVO VDS-4 • Renault RLD-3 • DDC 93K218 • Mack EO-O PP • Cummins CES 20081 • DEUTZ DQC III-10 LA • FORD WSS-M2C171-F1

SAE GRADE: 15W-30 / 15W-40 / 20W-50

API: CJ-4/SN

MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL CJ-4/SN is a high performance diesel engine oil that helps extend engine life in the most severe on and off-highway applications while delivering outstanding performance in modern, high-output, low-emission engines including those with EGR and After treatment Systems with Diesel Particulate Filters (DPFs) and Diesel Oxidation Catalysts (DOCs). It is recommended for use in a wide range of heavy duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries</p>	<ul style="list-style-type: none"> • API CJ-4/SN • ACEA E9 • MB 228.31 • Caterpillar ECF-3 • MAN M3477/3575 • VOLVO VDS-4 • Renault RLD-3 • DDC 93K218 • Mack EO-O PP • Cummins CES 20081 • DEUTZ DQC III-10 LA • FORD WSS-M2C171-F1

Available in





DIESEL ENGINE OIL

SAE GRADE: 0W-30 / 0W-40 / 5W-30 / 5W-40

API: CI-4/SL

FULLY SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL CI-4/SL is fully synthetic high performance heavy duty diesel engine oil that helps towards long engine life while providing long drain capability for modern diesel engines operating in severe applications. The high TBN level neutralizes the harmful effects of Sulphur contained in low quality diesel fuel. It delivers excellent performance in modern low emission engines, as well as older, well-maintained engines.</p>	<ul style="list-style-type: none"> • API CI-4/SL • ACEA E7, A3/B3/B4 • MB 228.3 / 229.1 • MAN M3275-1 • Volvo VDS-3 • Deutz DQC III-10 • JASO DH1 • MACK EO-N • Cummins CES 20076/20077/78 • Global DHD-1 • Renault RLD-2 • MTU Type 2 • Allison C4 • Caterpillar ECF 1a, ECF 2 • DDC 93K215

SAE GRADE: 10W-30 / 10W-40

API: CI-4/SL

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL CI-4/SL is Semi Synthetic is a heavy-duty engine oil that provides excellent lubrication in today's diesel and gasoline engines operating in severe applications. It is designed using the high performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention and volatility control. Momenta Nano is engineered to provide a strong foundation for oxidation resistance, soot handling, and wear control. It provides excellent piston deposit protection and reduced sludge formation to help provide long engine life.</p>	<ul style="list-style-type: none"> • API CI-4/SL • ACEA E7, A3/B3/B4 • MB 228.3 / 229.1 • MAN M3275-1 • Volvo VDS-3 • Deutz DQC III-10 • JASO DH1 • MACK EO-N • Cummins CES 20076/20077/78 • Global DHD-1 • Renault RLD-2 • MTU Type 2 • Allison C4 • Caterpillar ECF 1a, ECF 2 • DDC 93K215

SAE GRADE: 15W-30 / 15W-40 / 20W-50 / 20W-60

API: CI-4/SL

MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL CI-4/SL is a high performance diesel engine oil that provides excellent lubrication to diesel engines. It maximizes performance in the latest US, European and Japanese heavy duty diesel engines including severe applications such as high loads and multi trailer applications. It exhibits outstanding detergent, dispersant and anti-wear properties to keep the engine clean and enable efficient control of soot, sludge and piston deposits.</p>	<ul style="list-style-type: none"> • API CI-4/SL • ACEA E7, A3/B3/B4 • MB 228.3 / 229.1 • MAN M3275-1 • Volvo VDS-3 • Deutz DQC III-10 • JASO DH1 • MACK EO-N • Cummins CES 20076/20077/78 • Global DHD-1 • Renault RLD-2 • MTU Type 2 • Allison C4 • Caterpillar ECF 1a, ECF 2 • DDC 93K215





DIESEL ENGINE OIL





DIESEL ENGINE OIL

SAE GRADE: 0W-30 / 0W-40 / 5W-30 / 5W-40

API: CH-4/SJ

FULLY SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL CH-4/SJ is a fully synthetic diesel engine oil with hydro synthetic basis for modern diesel engines with and without turbo-charge. Provides high pump ability at cold cranking, providing safe lubrication and wear-out protection. Has optimal viscosity at wide-ranging temperatures. Satisfies the requirements of new engine types with prolonged oil-change interval.	<ul style="list-style-type: none"> • API CH-4/SJ • MB 228.3 • MAN 3275 • ACEA E7, A3/B3/B4 • VOLVO VDS-2 • Renault RLD-2 • MTU Type 2 • JASO DH1 • Mack EO-M/EO-L • Cummins CES 20076 • DFS 93K215 • DQC III-10

SAE GRADE: 10W-30 / 10W-40

API: CH-4/SJ

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL CH-4/SJ semi synthetic is a heavy duty diesel engine oil which helps to protect against the build-up of piston deposits for continuing engine efficiency. Exceeds performance limits in piston ring, cylinder liner and valve train wear tests for long engine life.	<ul style="list-style-type: none"> • API CH-4/SJ • MB 228.3 • MAN 3275 • ACEA E7, A3/B3/B4 • VOLVO VDS-2 • Renault RLD-2 • MTU Type 2 • JASO DH1 • Mack EO-M/EO-L • Cummins CES 20076 • DFS 93K215 • DQC III-10

SAE GRADE: 15W-30 / 15W-40 / 20W-50

API: CH-4/SJ

MINERAL

Description	Performance Level: (Meet & Exceed)
ALPHA OIL CH-4/SJ is a heavy duty mineral diesel engine oil. It contains unique additives providing high anti wear-out and energy-efficient properties. It guarantees safe lubrication even at cold temperatures. It effectively prevents sludge formation. It is designed for all modern engine types with and without turbochargers, multi-valve and with direct injection.	<ul style="list-style-type: none"> • API CH-4/SJ • MB 228.3 • MAN 3275 • ACEA E7, A3/B3/B4 • VOLVO VDS-2 • Renault RLD-2 • MTU Type 2 • JASO DH1 • Mack EO-M/EO-L • Cummins CES 20076 • DFS 93K215





DIESEL ENGINE OIL

SAE GRADE: 0W-30 / 0W-40 / 5W-30 / 5W-40

API: CG-4/SJ

FULLY SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL CG-4/SJ is fully synthetic diesel engine oil designed for the most severe performance requirements of highly powered turbocharged engines of leading automobile companies. This oil is fuel saving and reduces maintenance expenses for machines and engines. Resists oil thickening and the formation of carbon, varnish and sludge deposits. Helps prolong engine life.	<ul style="list-style-type: none"> • API CG-4/SJ • MB 228.3 • ACEA A3/B4 • MAN 3275 • VOLVO VDS • MTU Type-2 • MACK EO-L • Allison C4

SAE GRADE: 10W-30 / 10W-40

API: CG-4/SJ

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL CG-4/SJ is semi synthetic diesel engine oil designed for the most severe performance requirements of highly powered turbocharged engines of leading automobile companies. This oil is fuel saving and reduces maintenance expenses for machines and engines. Resists oil thickening and the formation of carbon, varnish and sludge deposits. Helps prolong engine life.	<ul style="list-style-type: none"> • API CG-4/SJ • MB 228.3 • ACEA A3/B4 • MAN 3275 • VOLVO VDS • MTU Type-2 • MACK EO-L • Allison C4

SAE GRADE: 15W-30 / 15W-40 / 20W-50

API: CG-4/SJ

MINERAL

Description	Performance Level: (Meet & Exceed)
ALPHA OIL CG-4/SJ is a premium high performance non-friction modified mineral engine oil. It contains a combination of high technology additives, including increased dispersant levels and low shear viscosity modifiers. It protects against corrosion, oil oxidation and sludge under all operating conditions.	<ul style="list-style-type: none"> • API CG-4/SJ • MB 228.3 • ACEA A3/B4 • MAN 3275 • VOLVO VDS • MTU Type-2 • MACK EO-L • Allison C4

Available in





DIESEL ENGINE OIL

SAE GRADE: 10W-30 / 10W-40

API: CF-4/SJ

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL CF-4/SJ is a premium quality diesel engine oil. This oil is designed for the most severe performance requirements of modern, highly rated turbo charged diesel engines in the road transport fleet applications and also off highway operations. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and offers adequate corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations.</p>	<ul style="list-style-type: none"> • API CF-4/SJ • MB 228.2 • ACEA E2-96, A3/B3 • MTU Type-2 • MAN 3275-1 • VOLVO VDS • MACK EO/K2 • CES 20075/74/73

SAE GRADE: 15W-40 / 20W-50 / 20W-60 / SAE 70 / SAE 60 / SAE 50

API: CF-4/SJ

MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL CF-4/SJ is a high performance heavy duty engine oil based on high quality mineral base stocks and advance additives technology providing superior dispersancy/detergency, wear and oxidation resistance properties. Ideal for mixed fleet use having a variety of different makes of heavy duty diesel engines and using fuels of a wide range.</p>	<ul style="list-style-type: none"> • API CF-4/SJ • MB 228.2 • ACEA E2-96, A3/B3 • MTU Type-2 • MAN 3275-1 • VOLVO VDS • MACK EO/K2 • CES 20075/74/73





DIESEL ENGINE OIL

Alpha Diesel Oil Protects and Cleans The Engine to Give You A More Comfortable Ride.





DIESEL ENGINE OIL

SAE GRADE: 15W-40 / 20W-50 / 20W-60 / SAE 70 / SAE 50 / SAE 40

API: CF/SF

MINERAL

Description	Performance Level: (Meet & Exceed)
ALPHA OIL CF/SF is a mineral oil based product recommended for use as single oil in mixed fleets with both light and heavy-duty engines. It is blended with an optimized combination of base oils and balanced additive system. Suitable for diesel and naturally aspirated gasoline engines used in trucks and passenger cars operating under harsh driving conditions. It provides exceptional thermal stability at high temperatures.	<ul style="list-style-type: none"> • API CF/SF • ACEA E2-96/A3/B3 • MB 228.2 • MIL-L-2104E • CAT TO-2 • MAN 270 • MTU TYPE 1 • ALLISON C4

SAE GRADE: 15W-40 / 20W-50 / 20W-60 / SAE 70 / SAE 50 / SAE 40

API: CD/SF

MINERAL

Description	Performance Level: (Meet & Exceed)
ALPHA OIL CD/SF is a heavy duty mineral diesel engine oil formulated with an optimized combination of base oil and a balanced additive system. It provides good protection against rust and corrosion, thermal and oxidation stability. It Control sludge build up and deposits hence prolongs equipment life and reduces maintenance costs.	<ul style="list-style-type: none"> • API CD/SF • MIL-L-2104D • CAT TO-2

SAE GRADE: 15W-40 / 20W-50 / 20W-60 / SAE 50 / SAE 40

API: CC/SC

MINERAL

Description	Performance Level: (Meet & Exceed)
ALPHA OIL CC/SC is a mineral diesel engine oil recommended for the lubrication of diesel engines and naturally aspirated gasoline engines used in commercial and passenger vehicles operating under mild driving conditions.	<ul style="list-style-type: none"> • API CC/SC • MIL-L-2104B





PETROL ENGINE OIL

SAE GRADE: 0W-20 / 5W-20 / 5W-30 / 10W-30

API: SP

SYNTHETIC / SEMI SYN

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SP engine oils are designed for use in passenger cars and light truck applications. These oils are engineered to provide the highest levels of engine protection available. These premium engine oils contain ultra pure base oils and a technologically advanced additive system which provides improved oxidation resistance, improved deposit protection, better wear protection, excellent low temperature performance and enhanced fuel economy.	<ul style="list-style-type: none"> • API SP / RC • ILSAC GF-6A • GM DEXOS1 GEN 2 (SAE 0W-20, 5W-20, 5W-30) • Ford WSS-M2C947-A, M2C930A, M2C153 (SAE 5W-20) • Ford WSS-M2C946-A, M2C92A (SAE 5W-20) • Chrysler MS-10797 • Chrysler MS-6395M (SAE 5W-20)

SAE GRADE: 0W-16

API: SP

FULLY SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SP 0W-16 is a fully synthetic ultra low viscosity multi-grade engine oil formulated for use in passenger cars specifying the use of oil meeting API SP, ILSAC GF-6B requirements. These oils are engineered to provide the highest levels of engine protection available. These premium engine oils contain synthetic base oils and a technologically advanced additive system which provides improved oxidation resistance, improved deposit protection, better wear protection, excellent low temperature performance and enhanced fuel economy.	<ul style="list-style-type: none"> • API SP • ILSAC GF-6B

SAE GRADE: 5W-40 / 10W-40 / 20W-50

API: SP

SYN / SEMI SYN / MIN

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SP multi-grade high mileage engine oils are engineered to provide outstanding engine protection in passenger cars and light truck applications. These engine oils contain highest quality base oils and a technologically advanced additive system which includes detergents, dispersants, anti-wear and anti-friction agents as well oxidation and corrosion inhibitors. This engine oils deliver exceptional protection and performance characteristics over the full service interval.	<ul style="list-style-type: none"> • API SP

Available in





PETROL ENGINE OIL

SAE GRADE: 0W-20 / 0W-30 / 0W-40 / 5W-30 / 5W-40

API: SN/CF

FULLY SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SN/CF is fully synthetic engine oil formulated for the highest level of protection demanded by high performance engines. It protects better than conventional engine oils in hot or cold operating temperatures helping to prevent dirt and build-up, for better response and improved performance, thus helping your engine to operate at its full potential. It meets the requirements of the latest industry standards for "Full SAPS" passenger car lubricants and outperforms conventional oils.	<ul style="list-style-type: none"> • API SN/CF • ACEA A3/B3/B4 • ACEA A5/B5 (HTHS <3.5) • Porsche A40 • MB 226.5/229.3/229.5 • Renault RN0700/RN0710 • VW 501 01 / 502 00 / 505 00 • OPEL GM-LL-B-025 • PSA B71 2296 • Ford WSS-M2C937-A • Ford WSS-M2C913-C/D (SAE 5W-30) • Ford WSS-M2C925-B (SAE 0W/5W-20)

SAE GRADE: 10W-30 / 10W-40

API: SN/CF

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SN/CF is an advanced semi synthetic lubricant featuring Full SAPS (Sulfated Ash, Phosphorous, Sulfur) technology, specifically designed for powerful and recent cars fitted with large displacement engines, Gasoline and Diesel, direct or indirect injection, with or without turbo. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low temperature performance over the life of the oil.	<ul style="list-style-type: none"> • API SN/CF • ACEA A3/B3/B4 • MB 229.5/229.3/226.5 • Renault RN0700/RN0710 • VW 501 01 / 502 00 / 505 00

SAE GRADE: 15W-30 / 15W-40 / 20W-50

API: SN/CF

MINERAL

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SN/CF mineral oils are formulated from quality base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions. It is recommended for all high performance gasoline engine cars equipped with direct-injection, multi valve & turbo-charger technologies.	<ul style="list-style-type: none"> • API SN/CF • ACEA A3/B3/B4 • MB 229.1 • VW 5050 00





PETROL ENGINE OIL

SAE GRADE: 0W-20 / 0W-30 / 0W-40 / 5W-30 / 5W-40

API: SN/CF (ACEA C3)

FULLY SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL SN/CF is an advanced fully synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. It meets the requirements of "Mid SAPS" passenger car lubricants with 0.08% phosphorus and 0.8% sulphated ash levels. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low temperature performance over the life of the oil.</p>	<ul style="list-style-type: none"> • API SN/CF • ACEA C3, A5/ B5 (HTHS < 3.5) • Porsche A40 • MB 229.31/229.51/229.52 • Renault RN0700/RN0710 • BMW Longlife-04 • VW 502 00 / 505 01 • GM Dexos 2 • Ford WSS-M2C948-A/948-B (SAE 5W-20) • Volvo VCC RBS0-2AE (SAE 0W-20) • Ford WSS-M2C917-A

SAE GRADE: 0W-16 / 0W-20 / 5W-20 / 5W-30 / 5W-40 / 10W-30 / 10W-40 / 15W-40 / 20W-50

API: SN/RC / ILSAC GF-5

SYN / SEMI SYN / MIN

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL API: SN/RC / ILSAC GF-5 oils are formulated from quality fully synthetic base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions. It is recommended for all high performance gasoline engine cars equipped with direct-injection, multi valve & turbo-charger technologies.</p>	<ul style="list-style-type: none"> • API SN/RC GF-5 (0W-20, 5W-20, 5W-30, 10W-30) • API SN (0W-16, 5W-40, 10W-40, 15W-40, 20W-50) • ILSAC GF-5 (0W-20, 5W-20, 5W-30, 10W-30) • DEXOS 1 (0W-20, 5W-20, 5W-30) • FORD WSS-M2C-945A (5W-20) • FORD WSS-M2C-966A (5W-30) • FORD WSS-M2C-947A (0W-20) • GM 6094M (0W-20, 5W-20, 5W-30) • CHRYSLER MS 6395 (ILSAC GRADES)

Available in



1L

4L

5L

20L

25L

200L





PETROL ENGINE OIL

SAE GRADE: 0W-30 / 0W-40 / 5W-30 / 5W-40

API: SM/CF

FULLY SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SM/CF is a high quality synthetic lubricant that incorporates anti-wear protection, as well as protection against sludge and deposit formation. This multi-grade oil meets the API quality requirement (SM) for gasoline engine passenger cars, sport utility vehicles, vans and light trucks. This oil is designed to provide improved oxidation resistance, improved deposit protection, better wear protection and better low-temperature performance over the life of the oil.	<ul style="list-style-type: none"> • API SM/CF • ACEA A3/B3 • ACEA A1/B1 (HTHS <3.5) • VW 502 00 / 505 00 • RN 700, RN 710

SAE GRADE: 10W-30 / 10W-40

API: SM/CF

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SM/CF is an advanced semi synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low temperature performance over the life of the oil.	<ul style="list-style-type: none"> • API SM/CF • ACEA A3/B3 • MB 229.3

SAE GRADE: 15W-40 / 20W-50 / 20W-60

API: SM/CF

MINERAL

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SM/CF oils are formulated from quality base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and better low temperature performance over the life of the oil.	<ul style="list-style-type: none"> • API SM/CF • ACEA A3/B3 • MB 229.1





PETROL ENGINE OIL

SAE GRADE: 0W-30 / 0W-40 / 5W-30 / 5W-40

API: SL/CF

FULLY SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SL/CF is fully synthetic motor oil is formulated using the unique additives technology that actively helps keep engines clean. It allows the product to provide higher levels of cleansing and protection. This oil is particularly suitable for turbo-compressed, multi-valve and direct injection engines. It meets the most difficult conditions of use (motorway, heavy urban traffic, etc.) during all seasons.	<ul style="list-style-type: none"> • API SL/CF • ACEA A3/B3 • ACEA A1/B1 (HTHS <3.5) • MB 229.3

SAE GRADE: 10W-30 / 10W-40

API: SL/CF

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SL/CF motor oil is formulated using the unique additives technology that actively helps keep engines clean. It allows the product to provide higher levels of cleansing and protection. This oil is particularly suitable for turbo-compressed, multi-valve and direct injection engines. It meets the most difficult conditions of use (motorway, heavy urban traffic, etc.) during all seasons.	<ul style="list-style-type: none"> • API SL/CF • ACEA A3/B3 • MB 229.3

SAE GRADE: 15W-30 / 15W-40 / 20W-50

API: SL/CF

MINERAL

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SL/CF is premium quality mineral oil for gasoline and diesel engines, which can be used in all operating conditions (city traffic, road, motorways). It is particularly suited to turbocharged engines and perfectly adapted to vehicles equipped with catalysts and using unleaded fuel.	<ul style="list-style-type: none"> • API SL/CF • ACEA A3/B3 • MB 229.1

Available in





PETROL ENGINE OIL

SAE GRADE: 0W-30 / 0W-40 / 5W-30 / 5W-40

API: SJ/CF

FULLY SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SJ/CF engine oil is a superior quality fully synthetic oil formulated with high performance base stocks and premium additive technology which helps deliver outstanding engine protection and prevent the build-up of dirt and sludge in older engines operating in all driving conditions in highways and in the city.	<ul style="list-style-type: none"> • API SJ/CF

SAE GRADE: 10W-30 / 10W-40

API: SJ/CF

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SJ/CF is semi synthetic engine oil a superior quality multi grade oil formulated with highly refined base stocks and premium additive technology which helps deliver outstanding engine protection and prevent the build-up of dirt and sludge in older engines operating in all driving conditions in highways and in the city.	<ul style="list-style-type: none"> • API SJ/CF

SAE GRADE: 15W-30 / 15W-40 / 20W-50

API: SJ/CF

MINERAL

Description	Performance Level: (Meet & Exceed)
ALPHA OIL SJ/CF mineral engine oil is a superior quality multi grade oil formulated with highly refined base stocks and premium additive technology which helps deliver outstanding engine protection and prevent the build-up of dirt and sludge in older engines operating in all driving conditions in highways and in the city.	<ul style="list-style-type: none"> • API SJ/CF





PETROL ENGINE OIL

SAE GRADE: 10W-30 / 10W-40

API: SG/CF

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL SG/CF semi synthetic oils for gasoline and diesel engines having high ageing resistance, effectively reduces carbon formation and high-temperature lacquer formation. Provides safe lubrication of the engine components. These oils contains low-ash additives which allow to prolong the endurance of the catalyst.</p>	<ul style="list-style-type: none"> • API SG/CF

SAE GRADE: 15W-30 / 15W-40 / 20W-50

API: SF/CD

MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL SF/CD is designed to be used for passenger cars, light trucks as well as farm equipment, especially where single type of oil is preferred. This oil contains inhibitors to combat acids formation, oxidation and foaming. It is formulated with high quality mineral base stock and advance additive system.</p>	<ul style="list-style-type: none"> • API SF/CD



Available in





MOTOCYCLE OIL 2 STROKE ENGINE

SAE GRADE: 20 / 30

API: TC

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL 2T is a semi synthetic lubricant which is designed to provide excellent performance in two stroke engines like motorcycles, scooters and mopeds. Its composition is perfectly compatible with lead-free fuels. This is a high technology product combining a perfect balance of highly refined semi synthetic base stocks and the latest additive's technology. It is specially formulated for use in oil injected as well as premixed gasoline/oil lubricated engines. Its increased performance provides protection against exhaust emissions and engine carbon deposits.</p>	<ul style="list-style-type: none">• API TC• JASO FD• ISO EGD

Available in



1L



4L



5L



20L



25L



200L





MOTOCYCLE OIL 4 STROKE ENGINE

SAE GRADE: 10W-30 / 10W-40 / 15W-40

API: SN

SEMI SYNTHETIC / MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL 4T is a high-performance engine oil formulated specifically to meet the demanding needs of motorcycle engines. It is primarily for on-road, high-performance, 4-cycle sport bikes, however, it may be used in other types of on and off-road 4-cycle motorcycles. It is formulated to help offer outstanding protection in 4-cycle, V-Twin type engines, particularly those which are air cooled and tend to run hotter than other types of engines. ALPHA OIL 4T provides excellent performance in common engine/transmission lubrication system or where the engine lubrication system is separate from the transmission system.</p>	<ul style="list-style-type: none"> • API SN • JASO MA2 • JASO MB

SAE GRADE: 10W-30 / 10W-40 / 15W-40

API: SL

SEMI SYNTHETIC / MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL 4T is a high quality engine oil designed for 4-stroke motorcycles. ALPHA OIL 4T is based on premium quality base oils and advanced additives to bring out the best in your machine. It is designed to ensure maximum power and performance, even under the most demanding riding conditions. Its anti-friction formula tion is proven to increase acceleration compared to conventional motorcycle oils. ALPHA OIL 4T protects the engine, clutch, gears and allows the best functionality of these three critical areas of the motorcycle.</p>	<ul style="list-style-type: none"> • API SL • JASO MA2 • JASO MB



Available in





CNG ENGINE OIL

SAE GRADE: 15W-30 / 15W-40 / 20W-50

API: CF

MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL API CF is a high performance heavy duty engine oil formulated specifically for spark ignited CNG and LNG fueled truck, bus engines and small to medium size CNG generators. It provides excellent performance in the challenging operating environment presented by CNG (Compressed Natural Gas) and LNG (Liquefied Natural Gas) and offers extended drain interval capability.</p>	<ul style="list-style-type: none"> • API CF • Cummins: CES 20074 • Detroit Diesel: DDC 93K216

SAE GRADE: 15W-30 / 15W-40 / 20W-50

API: SM

MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL API SM is a performance proven engine lubricant designed to provide faster and cleaner engine protection to make sure of longer engine life. It is designed for use in gas fueled engines in passenger car and light commercial vehicles. It has special additive system which resists wear under all operating conditions by forming a protective layer on contact surfaces. High viscosity index provides additional protection against wear at start-up and under high temperature operating conditions.</p>	<ul style="list-style-type: none"> • API SM • Suitable for use also where API SL, SJ or SG oils are specified

SAE GRADE: 15W-30 / 15W-40 / 20W-50

API: SG

MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL API SG is developed as a special long drain engine oil for three wheeler vehicles fitted with spark ignited CNG and LNG fueled light-duty engines. It provides excellent performance in the challenging operating environment presented by CNG (Compressed natural Gas) and LNG (Liquefied Natural Gas) and offers extended interval capability.</p>	<ul style="list-style-type: none"> • API SG





AUTOMATIC TRANSMISSION FLUID

Chrysler ATF+4

SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL ATF+4 automatic transmission fluid is designed for use in most types of Japanese, Korean, and Chrysler vehicles that require ATF+4 or prior specifications. This chemistry offers excellent low temperature properties and improved anti-shudder properties. ALPHA OIL ATF+4 is recommended for use in all transmissions, hydraulic systems, and power steering units manufactured by American, European, Korean, Japanese and other manufactures from around the world specifying Chrysler ATF+4, ATF+3 or ATF+2 type fluids.</p>	<ul style="list-style-type: none"> • Chrysler ATF+4 • Chrysler MS-9602

Dexron VI

SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL Dexron VI is a fully synthetic transmission fluid recommended for use in passenger car and light truck automatic transmissions that require a GM Dexron VI or earlier generation fluid. Trans-missions include the following Aisin Warner models: AW TF-80SC / SD, AWF21, AF40-6, AM6,AW6A-EI, TF81SC, AF21, GA6F21WA (Mini).</p>	<ul style="list-style-type: none"> • JWS 3309, JWS 3324, T-IV, AW-1, NWS 9638 • AS 68RC (T IV) • AUDI/VW G-052-162-A1/A2 • BMW ETL-7045, 7045E, LA2634, ETL-8072B, 81 22 9 400 275 • CHRYSLER M1375.4 • FIAT (ALL VEHICLES) TYPO T-IV • GENERAL MOTORS DEXRON II/III/IIIH/VI • HONDA ACURA Z-1 PREMIUM, HONDAMATIC S • HYUNDAI / KIA SP IV, HYUNDAI SPH-IV • ISUZU BESCO ATF II, ATF III • JAGUAR ATF 3403 M115, JLM 20238 • LT 71141 • MAZDA ATF M III • MERCON LV • MITSUBISHI DIAMOND SP-IV • MB ZF 4 HP20, 236.1/5/6/7/8/9/236.41 • PEUGEOT ZF 4 HP20 • PORSCHE ATF 3403-M115 • SUBARU ATF, ATF HP • TOYOTA TYPE T-III, T-IV • TOYOTA WS • VOLVO T-IV • VOITH 55.6635 / VOLVO 97340 • ZF 5HP 18FL/19FL/24A • ZF 5HP 30 • ZFF TE-ML 09 • BMW P/N 833227542290 • CITROEN P/N PR 9980 • SAAB P/N 93165147 • TOYOTA P/N 08886-02305/08886-81015

Available in





AUTOMATIC TRANSMISSION FLUID

Dexron III

SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL Dexron III is a fully synthetic automatic transmission fluid formulated with premium, severely hydro processed base stocks and additives that helps provide oxidation and thermal stability, friction control, load-carrying ability, corrosion and wear protection. It helps protect against the formation of deposits, sludge, varnish, foam and provide outstanding durability.</p>	<ul style="list-style-type: none"> • GM DEXRON III, IIIH • FORD MERCON V, FNR5 • FORD ESP-M2C-138-CJ/166-H • MOPAR AS68RC • CHRYSLER ATF +3, ATF +4 • HONDA ATF Z-1 • HYUNDAI/KIA SP-II, SP-III, JWS 334/3317/3309 T4 • KIA RED-1 • IDEMITSU K17 • JASO 1A • JWS 3309 • JWS 3324, TIV • MAZDA ATF-M III, ATF-MV • MITSUBISHI DIAQUEEN ATF J2, J3, SP-II, SP-III, PA • NISSAN 402, NISSAN MATIC-D, J, K • SUBARU ATF, ATF-HP • SUZUKI 3314, 3317 • TOYOTA T, T-II, T-III, T-IV (JWS 3309) • AUDI G052 162, G052 990, G 055 025, G 052 540, G 055 005, G 055 162 • VW TL 52162 • BMW LA 2634, LT 71141 • ETL 7045E • ETL-8072B • MB 236.1 / 2 / 3 / 5 / 6 / 7 / 9 / 11 • MB 236.12 / 14 / 15 / 41 • PSA AL-4 • RENAULT DP-0 • TEXACO N402 • ZF TE-ML 09, 11A/11B • ZF TE-ML 04D, 09, 11B, 14A, 14B, 16L, 17C • SAAB 3309 • VOLVO 4-6 SPEED • ALLISON TES 389 • ALLISON TES 228(C4) • MAZDA F-1/JWS 3317/ M-III/TYPE-IV • SUBARU HP





AUTOMATIC TRANSMISSION FLUID

Dexron II

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL Dexron II is an automatic transmission oil blended with highly refined base stocks and one of the latest additive's technologies. It is used in passenger cars and light commercial vehicles. It helps reduce transmission "chatter" assuring a smooth and quiet operation at all speeds under any working condition. ALPHA OIL Dexron II provides optimal oxidation and thermal stability, friction control, cleanliness, load carrying ability, wear and corrosion protection to ensure the longest life of your transmission.</p>	<ul style="list-style-type: none"> • GM DEXRON IID/IIIE • ALLISON TES 389, ALLISON TES 228(C4) • FORD ESP-M2C138-CJ / ESP-M2C166-H • MAN 339 TYPE L1/L2/Z1/V1 • CHRYSLER +3 • TASA • VOITH H55.6335 • VOLVO CE 97340/41 • MB 236.1/236.5/236.7236.8 • ZF TE-ML-03D / 05 / 21L / 09 / 11A / 11B / 14A / 17C • TOYOTA TII/2 • BMW 81 22 9 400 272/81 22 9 400 275/81 22 9 407 738 • CAT TO-2 • OPEL 19 40 700 / 19 40 707 • MITSUBISHI SP / SP2/ BTR

TYPE A

MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL Type A is a multi-purpose transmission fluid, designed for use in automatic gearboxes, where GM Type A Suffix A is quoted. Its special formula enables very smooth operation of torque converters and fluid couplings of automatic transmissions.</p>	<ul style="list-style-type: none"> • GM Type A Suffix A



Available in  1L  4L  5L  20L  25L  200L



AUTOMOTIVE GEAR OIL

SAE GRADE: 75W-80 / 75W-90 / 75W-140

API: GL-5

FULL SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL GL-5 is synthetic multi-purpose transmission oil for synchronized and non-synchronized manual transmissions and for axle transmissions, transfer cases, intermediate gear boxes, ancillary transmissions in vehicles and work machines. ALPHA OIL GL-5 is developed to eliminate seasonal transmission oil changes. The balanced additive combination warrants properties such as high pressure capacity, above average viscosity- temperature properties, high oxidation stability, low solidification points, good wear protection and prevents sludge.</p>	<ul style="list-style-type: none"> • API: GL-5 • API MT-1 • MIL-PRF-2105E • SAE J2360 • MAN 342 M2 • SCANIA STO 1:0 • ZF TE-ML 05A, 7A, 12E, 16B, C & D, 17B, 19B, 21A • MB 235.8 • VOLVO 97312

SAE GRADE: 80W-90 / 80W-140

API: GL-5

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL GL-5 semi synthetic multi-grade gear oil is recommended for manual transmissions and for axle transmissions, transfer cases, intermediate gear boxes, ancillary transmissions in vehicles and work machines requiring API GL-5 oil. ALPHA OIL semi synthetic is developed to eliminate seasonal transmission oil changes. The balanced additive combination warrants properties such as high pressure capacity, above average viscosity-temperature properties, high oxidation stability, low solidification points, good wear protection and prevents sludge.</p>	<ul style="list-style-type: none"> • API: GL-5 • API MT-1 • MIL-PRF-2105E • SAE J2360 • MAN 342 M2 • SCANIA STO 1:0 • ZF TE-ML 05A, 7A, 12E, 16B, C & D, 17B, 19B, 21A • MB 235.8 • VOLVO 97312

SAE GRADE: SAE 90 / SAE 140 / 85W-90 / 85W-140

API: GL-5

MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL GL-5 is a mineral oil based high-performance, high-pressure gear oil manufactured from carefully selected base oils and multifunctional extreme pressure additives. This hypoid gear oil is suitable for axle drives – especially for heavy-duty hypoid transmissions. It has excellent viscosity temperature properties.</p>	<ul style="list-style-type: none"> • API: GL-5 • API MT-1 • MIL-L-2105D • SAE J2360 • MAN 342 M2 • SCANIA STO 1:0 • ZF TE-ML 05A, 7A, 12E, 16B, C & D, 17B, 19B, 21A • MB 235.8 • VOLVO 97312





AUTOMOTIVE GEAR OIL

SAE GRADE: 75W-80 / 75W-90 / 75W-140

API: GL-4

FULLY SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL GL-4 is fully synthetic high-performance gear oil is a top grade, extreme pressure gear oil for high-load manual, auxiliary, transaxle and hypoid transmissions, where a lubricant complying with API GL4 is required. High-quality, synthetic-based oil and modern additive technology ensures a broad application range and optimum transmission lubrication under extreme conditions. The low-viscosity characteristics of this gear oil makes it also suitable where shifting difficulties exist (e.g. stiffness or noise generation).</p>	<ul style="list-style-type: none"> • API: GL-4 • ZF TE-ML 08 • MAN 341 (TYPE MB) • MB 235.11

SAE GRADE: 80W-90 / 80W-140

API: GL-4

SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL GL-4 is a semi synthetic blend fluid with effective additives for manual transmissions. A high load-carrying capacity guarantees an optimum gearbox lubrication even at high temperatures. This gear oil contains only high-quality paraffinic lubricating oils and the most technologically advanced additive system, which includes extreme pressure, anti-wear, anti-friction agents and oxidation and corrosion inhibitors.</p>	<ul style="list-style-type: none"> • API: GL-4 • ZF TE-ML 08 • MAN 341 • MB 235.10 • Massey Ferguson M1110

SAE GRADE: SAE 90 / SAE 140 / 85W-90 / 85W-140

API: GL-4

MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL GL-4 is mineral gear oil is specially formulated for multipurpose, extreme pressure applications, including conventional differentials, gear boxes, limited slip rear axles, manual transmissions and hypoid gears. Contains only high-quality paraffinic lubricating oils and the most technologically advanced additive system, which includes extreme pressure, anti-wear, anti-friction agents and oxidation and corrosion inhibitors.</p>	<ul style="list-style-type: none"> • API: GL-4 • ZF TE-ML 08 • MAN 341 • MB 235.10

Available in





AUTOMOTIVE GEAR OIL

SAE GRADE: 75W-80 / 75W-90 / 75W-140

API: GL-5 (Limited Slip)

SYNTHETIC / SEMI SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL GL-5 is developed for limited slip differential applications to withstand high loads and repeated shock-load conditions. Also ideal for conventional differentials and vehicles that operate under heavy duty conditions such as 4x4, towing, or carrying heavy loads. ALPHA OIL is formulated with high levels of extreme pressure additives and friction modifiers to protect the critical mechanisms of limited slip differentials.</p>	<ul style="list-style-type: none"> • API: GL-5 • WSS M2C939-A • SR-M2C9102-A • MIL-L-2105D

SAE GRADE: SAE 90 / SAE 140

API: GL-1

MINERAL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL oils GL-1 are rust and oxidation inhibited gear oils that are recommended for many automotive and industrial equipment where the equipment manufacturer recommends the use of a straight mineral oil with SAE viscosity grades 90 or 140. These gear oils are also suitable for lubrication of many types of equipment where copper or bronze is present and susceptible to attack by oils containing sulfur-phosphorus compounds.</p>	<ul style="list-style-type: none"> • API: GL-1





AUTOMOTIVE BRAKE FLUID

DOT 4

SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL DOT 4 is high quality synthetic brake and clutch fluid conforming to the DOT4 specifications and is based on poly glycol type fluids that is a general standard used in worldwide automotive brake equipment. The product is blended with special additives that prevent fluid oxidation, rust and the swelling of the piston seals used in conventional brake systems.</p>	<ul style="list-style-type: none"> • FMVSS 116 DOT 4 • ISO 4925 (CLASSES 4) • SAE J 1703 & J 1704 • FORD WSS-M6C57-A2 • FORD WSS-M6C65-A2 • JIS K 2233

DOT 3

SYNTHETIC

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL DOT 3 is high quality synthetic brake and clutch fluids conforming to the DOT3 specifications and are based on polyglycol type fluids that is a general standard used in worldwide automotive brake equipment. The product is blended with special additives that prevent fluid oxidation, rust and the swelling of the piston seals used in conventional brake systems.</p>	<ul style="list-style-type: none"> • FMVSS 116 DOT 3 • ISO 4925 • SAE J 1703



Available in





AUTOMOTIVE COOLANT

Concentration: 33% / 50% / 60% / 100%

COOLANT (OAT)

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL Coolant / Antifreeze is a ready-to-use, phosphate-free, silicate-free, nitrite-free and borate-free, ethylene glycol-based coolant that is designed to provide exceptional wet sleeve liner cavitation and corrosion protection of all cooling system metals. ALPHA OIL Coolant / Antifreeze formulated with organic corrosion inhibitors to provide total cooling system protection for on-road and off-road use.</p>	<ul style="list-style-type: none"> • BS 6580 • ASTM D3306

HYBRID (HOAT)

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL HYBRID is based on Hybrid Organic Acid Technology (HOAT) which provides protection against damaging rust and corrosion in automobiles and truck cooling systems including American, Asian, and European vehicles. This product is formulated to be phosphate-free and does not contain 2-Ethylhexanoic acid (2EH).</p>	<ul style="list-style-type: none"> • ASTM D3306, D4985, D6210 • BS 6580 • SAE J1034, J1941 • FORD WSS-M97B51-A1 • ANFOR NF R 15-601 • CATERPILLAR (DEAC) • CHRYSLER MS 7170 • CUMMINS • DETROIT DIESEL • JIS K 2234 • JOHN DEERE H-5, H24B1, H24C1 • TMC RP329, RP330





ISO VG Grade: 68 /100 / 150 / 220 / 320 / 460 / 680

EP GEAR OIL

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL EP gear lubricants are high performance, multipurpose mineral oil based lubricants designed for the lubrication of many types of industrial gear systems like spur, helical, and straight and spiral bevel types operating under severe and wide ranges of speeds, loads and temperatures. These oils are designed to provide outstanding wear protection and excellent thermal stability.</p>	<ul style="list-style-type: none">• DIN 51517 Part 3 CLP• ISO 12925-1:1996 CKD• AIST 224/US STEEL 224• ANSI/AGMA 9004-D95/9005-E02• DAVID BROWN S1.53.101• GM LS 2 EP GEAR OIL• FIVES CINCINNATI MACHINE GEAR• FLENDER





ISO VG Grade: 22 / 32 / 46 / 68 / 100 / 150

HLP DIN 51524-2

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL Industrial Hydraulic Oils meeting DIN 51524-2 HLP are high quality anti-wear hydraulic oils specially developed to satisfy the wide temperature variations and viscosity range encountered with modern hydraulic systems and meet the requirements of the world's leading hydraulic equipment manufacturers. The excellent demulsibility and VI of ALPHA OIL oils proves highly useful in a wide range of applications.</p>	<ul style="list-style-type: none"> • DIN 51524-2 HLP • VICKERS I-286-S, M-2950-S • DENISON HF-1, HF-2, HF-0 • CINCINNATI MILACRON P-68, P-69, P-70 • LEE NORSE 100-1 • B.F. GOODRICH 0152 • FORD M-6C 32 • AFNOR E 48-603 • US STEEL 126, 127

ISO VG Grade: 22 / 32 / 46 / 68 / 100 / 150

HVLP DIN 51524-3

Description	Performance Level: (Meet & Exceed)
<p>ALPHA OIL Industrial Hydraulic Oils meeting DIN 51524-3 HVLP provide excellent high temperature performance, high degree of shear stability and oxidation resistance. These oils are formulated to have a high viscosity index and a low pour point for use over a wider temperature range. They provide excellent wear protection and thermal stability at high temperatures to minimize deposit formation and provide long service life. They protect hydraulic system components against rust and corrosion.</p>	<ul style="list-style-type: none"> • DIN 51524-3 (HV) • DIN 51524-2 (HM)





CALCIUM GREASE

Description	Performance Level: (Meet & Exceed)
ALPHA OIL Calcium Greases consist of refined paraffinic base stock, calcium based thickener and special additive package. These greases possess good water resistance and can be used for lubrication of machine elements operating in conditions where water ingress cannot be avoided. These greases provide protection against rust, corrosion, wear and has outstanding ability to resist water washout.	<ul style="list-style-type: none">• NLGI 2• NLGI 3

LITHIUM EP GREASE

Description	Performance Level: (Meet & Exceed)
ALPHA OIL Lithium EP Grease is a Lithium thickened lubricating grease formulated with mineral base oil and improved with extreme pressure (EP) additives to lubricate and protect even in heavy loaded circumstances. Mechanically very stable and easily pump able due to its smooth consistency.	<ul style="list-style-type: none">• NLGI 0• NLGI 1• NLGI 2• NLGI 3

LITHIUM MP GREASE

Description	Performance Level: (Meet & Exceed)
ALPHA OIL Lithium MP Grease is multipurpose grease for general lubrication under normal operating conditions and loads, formulated for lubrication of all kinds of universal applications in transport, agriculture and off road equipment operating in wet, dusty and or dry conditions.	<ul style="list-style-type: none">• NLGI 2• NLGI 3



Available in





ALPHA OIL

Automotive, Industrial Lubricants and Greases





ALPHA OIL



Phone

Mobile : 01911151177
Mobile : 01720004147



Mail Address

asianpetrold@gmail.com
support@asianpetro.com.bd



Our Location

38-C Postogola DIT Plot, I/A
Shyampur, Dhaka-1204



Office Hour

Saturday-Thursday 9 AM-6 PM